



SUNGLAZE®

Solid Polycarbonate Standing Seam
Architectural System



Content

Typical Applications -----2

Panel Types -----3

Colours-----3

Project Gallery -----4

Typical Physical Properties-----6

Thermal Insulation -----6

Flammability-----6

Acoustic Properties-----7

Resistance to UV Radiation -----7

Chemical Characteristics -----7

System Principles -----7

System Components -----8

Installation Data-----9

Installation Guidelines -----10


Assembly Details -----12

Manufacturer’s Lifetime Warranty-----14



SUNGLAZE is an architectural system that offers smart design, elegant appearance, versatility, low maintenance and sustainable performance to various architectural challenges.

SUNGLAZE incorporates proprietary standing-seam profiling and glazing that enable wide spans and high loading capacity. It can be specified in various lengths to match different structures, including flat and curved designs. SUNGLAZE is easy to fasten, the panels are simply joined by an aluminum profile set that is enclosed at the ends by end-closures. Screws lock the system and fix it to the structure without any penetration through the panels. The Cap-plug completes the assembly, covering the screw head and provides a smooth appearance from above.



Typical Applications

- Architectural projects
- Commercial and retail
- Sports venues roofing
- Covered walkways
- Open markets
- Service stations
- Entrances
- Pool covers



Easy to Install



Glass-Like Appearance



Superior Load Capacity



Low Maintenance



Sealant-Free Installation



Leakproof



Scan for more information



Panel Types

SUNGLAZE solid polycarbonate panels are offered in 3mm, 4mm* and 6mm thickness. Panel width is determined by the system width, 600mm or 800mm. Maximum panel length is 11.9m (Typical stock length, equaling slightly

more than 39 feet). Standard SUNGLAZE panels include UV protection on one side (UV protection on both sides is optional for special orders).

Property	SUNGLAZE Type			
	3/600	4/600**	4/800*	6/800
Center to Center Width (mm)	600	600	800	800
Panel width (mm)	584	585	785	785
Height (mm)	20	21	21	21
Area Weigh	3.79 Kg/m ²	5.05 Kg/m ²	4.98 Kg/m ²	7.453 Kg/m ²
Linear Meter Weight	2.20 Kg/m	2.94 Kg/m	3.90 Kg/m	5.96 Kg/m
Min. Cold Bending Radius (m) For the polycarbonate panel	4.0 m	4.0 m	4.0 m	4.0 m
System weight	6.14 Kg/m	7.40 Kg/m	6.73 Kg/m	9.25 Kg/m

SUNGLAZE aluminum profiles must be roll formed separately to the desired radius, not below a minimum radius of 4m.

* stocked in Australia

** stocked in Australia in clear only

Colours

Colour		%LT	%Haze	SHGC	SC
		ASTM D-1003		ASTM E-424-71	
	Clear *	90	<1	0.87	1.00
	Bronze	20	<1	0.45	0.52
	Grey *	20	<1	0.44	0.51
	White Opal	28	100	0.32	0.37
	White Diffuser	80	100	0.87	1.00
	Solar Ice *	20	100	0.39	0.45
	Solar Control	*20	67	0.33	0.36
	Solar Olympic	20	50	0.41	0.47
	Smart Green	70	26	0.58	0.67
	Smart Blue	50	26	0.57	0.65
	Bluish Breeze *	70	1	0.55	0.63

Note: * Colours stocked within Australia. Other colours & Light transmissions are available upon request, subject to minimum quantity.

LT (Light Transmission)

The percentage of incident visible light that passes through an object.

SHGC (Solar Heat Gain Coefficient)

The percentage of incident solar radiation transmitted by an object, which includes the direct solar transmission and the part of the solar absorption radiated inward.

SC (Shading Coefficient)

The amount of the sun's heat transmitted through a given window compared with that of a standard 3mm thick single pane of glass under the same conditions.

Energetic Efficiency



SolarSmart™ are energy-efficient colors break the traditional ratio between light transmission and shading coefficient. SolarSmart™ panels block Infrared energy that causes heat buildup, and transmit "cool light" that reduces air-conditioning and lighting costs.





Project Gallery



Caddens Corner Shopping Centre, Australia

Application: Industrial Awning
SUNGLAZE Type: 4/800 Clear



Hindu Temple, Australia

Application: Pergola
SUNGLAZE Type: 4/800 Bluish Breeze



Bremerton Wines, Australia

Application: Pergola
SUNGLAZE Type: 4/800 Solar Ice



Anvers Confectionery, Tasmania, Australia

Application: Roof and window glazing - 80 sqm (900 sqft)
SUNGLAZE Type: 4/800 Grey



H2O Southport, Australia

Application: Industrial Pergola
SUNGLAZE Type: 4/800 Clear



Residential, Coomera, Australia
Application: Pergola
SUNGLAZE Type: 4/800 Bluish Breeze



Burnie Cheese Factory, Tasmania, Australia
Application: Industrial Sidelights
SUNGLAZE Type: 4/600 Grey



The Barker Hotel, Australia
Application: Pergola
SUNGLAZE Type: 4/800 Clear



Pergola, Sydney, Australia
Application: Pergola
SUNGLAZE Type: 4/800 Clear



Residential Pergola, Australia
Application: Pergola
SUNGLAZE Type: Solar Ice



Typical Physical Properties

Property	Method*	Conditions	Units	Value
Mechanical				
Density	D-792		g/cm³	1.2
Tensile modulus of elasticity	D-638	1 mm/min	Mpa	2,300
Flexural strength	D-790	1 mm/min	Mpa	93
Flexural modulus	D-790	1.3 mm/min	Mpa	2,600
Notched impact strength Izod	D-256	23°C	J/m	800
Impact falling dart	ISO 6603/1d	3mm		158
		4mm	J	180
		6mm		>310
Impact - fall through	E-695		m/kg	336
Charpy Impact after Xenon Arc Exposure (D-6110)	D-2565-08	3000 hrs	% Loss of Impact Strength	<10
Thermal				
HDT (Heat Deflection Temperature)	D-648	Load: 1.82Mpa	°C	135
Vicat softening temperature	D-1525	Load: 1kg	°C	150
Service temperature - Short term			°C	-50 to 120
Service temperature - Long term			°C	-50 to 100
Coefficient of linear thermal expansion	D-696		cm/cm °C	6.5 x 10 ⁻⁵
Thermal conductivity	C-177		W/m °K	0.21
Specific heat capacity	C-351		kJ/kg °K	1.3
Weathering				
Color change	D-2244	60 months	ΔE	<3
Yellowing index	E-313	60 months	Δ Yellowness Index	<10
Light transmission	D-1003	10 years	%	<6
Leakage / Structural				
Water leakage	E-283	20 psf		none
Air leakage	E-331	6.24 psf (Condition of air leakage test)	cfm/ft²	0.05
Uniform load	E330 / TAS 202-94		psf	+/- 150psf (ULS)

*Properties in the table relate to the polycarbonate glazing panels in the Sunglaze system. **ASTM method except where noted otherwise.

*** All tests results are pending sheet thickness.

Thermal Insulation

The attached table compares “U” values of glass and SUNGLAZE panels of equivalent thickness. For any given thickness, the “U” value of SUNGLAZE is better than that of glass. This can result in a significant 6.5-9% reduction in energy expenditure both for heating in winter and air-conditioning during the summer time. Note that the use of SolarSmart™ panels will partially block heat generating infrared solar energy, which will further assist in reducing the air-conditioning costs during summer time.

Thickness	SUNGLAZE U-Value [W•m²•K]	Glass U Value [W•m²•K]
3 mm	5.43	5.79
4 mm	5.29	5.76
6 mm	5.04	5.52

Flammability

SUNGLAZE complies with the most demanding international fire resistance standards in the field of plastics, as indicated in the detailed table herein. The classification is subject to product type, thickness and color.

Product	Standard	Classification*
SUNGLAZE	EN13501	B, s1, d0
	ASTM D-635	CC1
	ASTM D-1929	628°C
	ASTM D-2843	Smoke Density <75
SUNGLAZE FR	E-84	Class A

* For more detailed information please contact your Palram distributor.



Acoustic Properties

SUNGLAZE panels sound insulation properties are indicated in the table to the right. The attenuation of sound waves together with its impact resistance, has made SUNGLAZE a material of choice for cladding.

Thickness	Acoustic Insulation DIN 52210-75 RW (db)
3mm	23
4mm	24
6mm	26


* For more detailed information please contact your Palram distributor.

Resistance to UV Radiation

Palram polycarbonate panels retain their mechanical properties and transparency throughout a long time of external service due to Integrated co-extruded UV protection. The protection will not peel off over time. The attached graph presents typical results from SUNGLAZE panels tested under accelerated weathering (QUV exposure simulation) that is equivalent to 20 years of actual field exposure. The light transmission of SUNGLAZE was essentially stable.

Chemical Characteristics

A wide listing of Palram's polycarbonate sheets resistance to chemical agents is available from the Chemical Resistance of Palram Polycarbonate Products brochure at Palram websites. For more details please contact your Palram distributor.



System Principles

Glazing Set

The Base is an extruded aluminum profile in natural anodize finish. Its maximum length is 7m. The Base is the lower part of the glazing set, placed under the panels and fixed to the structure by the Fixing screws.

The Cap is an extruded aluminum profile in natural anodize finish. Its maximum length is 7m. The Cap is the upper profile of the glazing assembly, positioned onto the panel raised edges and Base, and attached to the Base by the Locking screws.

The Cap-Plug is 19.5mm wide aluminum strip in natural anodize finish. Its maximum length is 7m. The Plug is snapped into place onto the Cap, concealing the Locking screws from the top, and providing a smooth surface.

Screws


The fixing screw is a cross-head self drilling screw, 4.8x19mm (#10x0.75") for metal structure and a cross-head selftapping screw, 4.8x25mm (#10x1") for wood structure.

These screws fix the Base to the structure.

The locking screws are cross-head tapping screw, 5.5x19mm (#12x0.75") for 3&4mm and 5.5x25mm (#12x1") for 6mm. These screws attach the Cap onto the Base.

End Closure

These anodised finished aluminum plates plug at both ends of the profiles assembly.





System Components

Component	Drawing	Thickness	Finish	Suppliance Data
Inner Profile Base		3mm	Anodize	Length: Up to 7m
		4 mm**		
		6 mm		
Side Base		3mm	Anodize	Length: Up to 6m
		4 mm**		
		6 mm*		
EPDM Gasket		3mm	Black	Length: 10/25m rolls
		4 mm**		
		6 mm*		
Inner Profile Cap		3mm	Anodize	Length: Up to 7m
		4 mm**		
		6 mm		
Side Cap		3mm	Anodize	Length: Up to 7m
		4 mm**		
		6 mm*		
Cap Plug (For inner & Side Cap)		3mm	Anodize	Length: Up to 7m
		4 mm**		
		6 mm		
Inner Profile End Closure		3mm	Anodised finish	Each
		4 mm**		
		6 mm		
End Profile End Closure		3mm	Anodised finish	Each
		4 mm**		
		6 mm*		
Spanbar 65x65 & 100x65mm* (*stocked)		3mm*	Powder Coat / Anodize	Length: Up to 7m
		4 mm* **		
		6 mm*		
Pan Phillips Self Drilling Fixing Screw		3mm	4.8x19	Nickel Zinc Pack of 50
		4 mm**	4.8x19	
		6 mm	4.8x19	
Pan Phillips Locking Screw		3mm	5.5x19	Nickel Zinc Pack of 50
		4 mm**	5.5x19	
		6 mm	5.5x25mm	
Pan Phillips Self Tapping Fixing Screw for timber		3mm	4.8x25mm	Nickel Zinc Pack of 50
		4 mm**	4.8x25mm	
		6 mm	4.8x25mm	

* Available per minimum quantity ** Available Locally




Installation Data

Roof Structure

SUNGLAZE system is designed for both rafter and purlin construction options, flat or curved. The recommended minimum roof slope for SUNGLAZE applications is 5%. For lower slopes - rafter design is recommended.

Assembled System Width



Maximum Spans Between Purlins

Type (mm)	Rafter Centers (mm)	Single Span (mm)					
							
		75	100	125	150	175	200
		kg/m ²	kg/m ²	kg/m ²	kg/m ²	kg/m ²	kg/m ²
SUNGLAZE 3/600	600	900	820	760	NA	NA	NA
SUNGLAZE 4/600	600	900	820	760	720	680	NA
SUNGLAZE 4/800	800	820	745	690	NA	NA	NA
SUNGLAZE 6/800	800	900	820	760	720	680	650

Type (mm)	Rafter Centers (mm)	Multi Span (mm)											
		Mid-Span (mm)						End-Span (mm)					
													
		75	100	125	150	175	200	75	100	125	150	175	200
		kg/m ²						kg/m ²					
SUNGLAZE 3/600	600	1540	1400	1300	NA	NA	NA	1210	1100	1020	NA	NA	NA
SUNGLAZE 4/600	600	1540	1400	1300	1220	1160	1110	1210	1100	1020	960	910	870
SUNGLAZE 4/800	800	1400	1275	1180	NA	NA	NA	1100	1000	925	NA	NA	NA
SUNGLAZE 6/800	800	1540	1400	1300	1220	1160	1110	1210	1100	1020	960	910	870

Notes:

1. The values are based on maximal deflection criteria of L/200 for the aluminum profiles and L/20 for the Polycarbonate panels.
2. The dimensions depicted do not supersede the requirements of local construction codes.
3. In case of rafter installation, the distance between fixing screws should be 500 mm.

Cyclonic installation available please contact a Palram representative.



Installation Guidelines

A • Cut to Size	B • Pre-Drilling	C • Profile End Closure (Top & Bottom)
D • Fix Inner Base Profile	E • Fix Next Inner Base Profile	F • Position First Panel
G • Fix Inner Cap Profile	H • Assemble Cap Plug	I • Remove Outer Masking
J • Cut Side Panels To Size	K • Fix Side Base Profile	L • Fix Side Cap Profile

Notes:

1. The SUNGLAZE system does not require the use of silicones or adhesives for parts interfaces. For sealing of flashing assemblies' use only Palram approved accessories, silicones, sealing tape, and closure fixtures etc.
2. To clean SUNGLAZE panels, use a pressure washer with a fanned spray nozzle and allow natural drying. Do not use cloth, sponge, chamois or similar accessories. Doing this might scratch the panels and harm their appearance.



A ▪ Cut to Size

Cut the aluminum profiles to length, allowing for overhangs of up to 150mm at each end. An overhang minimum of 50mm over the end-purlin into the gutter is recommended. Cut the panels 10mm shorter than the aluminum profiles if the roof length is shorter than 3 meters, and 20mm shorter than the aluminum profiles if the roof length is 3 meters, up to 6 meters for expansion allowance. Use a circular saw or hand saw with fine tooth blades and moderate feeding rate for easier and finer cutting.

B ▪ Pre-Drilling

NOTE: When installing over a structure skip to step C.

When installing over a wood structure, measure the purlin distance and pre-drill 6mm screw holes in each End Base Profile and Inner Base Profile. Take into consideration the overhangs over both ends.

C ▪ Profile End Closure

On ground level, fasten the end closures to the top and bottom ends of every End Profile Base and Inner Profile Base.

D ▪ Fix the inner base profile

Set the first inner base profile at the precise centerline of the supporting structure and fix it to the structure using the provided fixing screws. Fix two screws at each purlin or by the recommended span on rafters. Locate the fixing screws at both base sides - two screws for every junction between base and structure.

E ▪ Fix next inner base profile

Locate the center line of the next inner base profile at 602mm (for 3/600 and 4/600) or 802mm (for 4/800 and 6/800) from prior inner base center line, and fix it as described in step D.

IMPORTANT! Measure and mark the inner base profile centerline at every purlin, or at every screw location on a rafter. It is highly advisable to prepare and use a spacer rod. (Note: in order to avoid accumulated deviations, do not fix more than 1-2 base profiles ahead of the actual assembly).

Remove inner masking

Remove the protective masking from the bottom surface of the panel (the face to contact the supportive structure). Keep the unprotected side away from the roof structure until final positioning of the panel, to avoid scratching.

F ▪ Position first panel

Position the first panel onto the base. Make sure the panel is correctly seated along its entire length.

G ▪ Fix inner cap profile

After two adjacent roof panels are in place, position the inner cap profile onto the inner base profile and panel edges. Fix the inner cap profile with the provided locking screws through every hole into to the inner base profile. The screws on both ends of the inner cap should be located a maximum of 50mm from each profile end. (Note: Drill an additional 6mm hole at the end of the inner cap profile if needed).

H ▪ Assemble cap plug

Snap the cap plug into place on top of the inner cap profile using a rubber mallet, performing moderate strikes with short intervals. Use a piece of wood to disperse the impact of the mallet and avoid damage to the profile pieces.

Repeat stages steps 4 to 10 until all inner panels (except of the edge panels) are installed.

I ▪ Remove outer masking

Remove the protective masking from the panel's external face shortly after installation. Delaying the removal of the masking can make it very difficult to remove later. (Note: On hot days remove the top protective film immediately after installation to prevent the film from bonding to the panel!)

J ▪ Cut end panels to size

Determine the required width of the end panels and cut them to size. Use a circular saw or hand saw with fine tooth blades. They should also have a moderate feeding rate for easier and finer cutting. (Note: Sometimes the end panel does not need to be cut).

K ▪ Fix side base profile

If the end panel was cut, on ground level, set the provided EPDM gasket along the end panel cut edge and insert the end base profile onto it. Take the assembly to the roof and fix it to the structure using the provided fixing screws.

If the end panel was not cut, fix the end base profile to the structure as described in step 5. Make sure the open channel is facing out.

L ▪ Fix end cap profile

Position the end cap profile onto the end base profile and panel edges. Fix the end cap profile with the provided locking screws through every hole and into to the end base profile. The screws on both ends of the end cap profile should be located at a maximum of 50mm from each profile end. (Note: Drill an additional 6mm hole at the end of the inner cap profile if needed).

Assemble cap plug

Snap the cap plug into place on top of the end cap profile using a rubber mallet, performing moderate strikes with short intervals. Use a piece of wood to disperse the impact of the mallet and avoid damage to the Profile pieces.

Side flashings

These purpose made flashings are not supplied by Palram and are used on the structure sides as a flashing.



Scan for installation Guide




Assembly Details


The drawings below are available for download as CAD files from the SUNGLAZE web page from Palram websites.

Please note: The drawings show suggested installation procedures for SUNGLAZE. All parts shown in the drawings aside from the system components are not provided by Palram.


Wall - Roof detail




Gutter detail




Ridge Cap detail



Side flashing



Cut end panel



Whole end panel

NATSPEC

Manufacturer's Lifetime Warranty

SUNGLAZE panels are guaranteed for water leak-proof performance for 25 years. SUNGLAZE panels bear a limited lifetime warranty not to lose more than 6% of light transmission for 10 years and no more than 1% per year thereafter, when measured according to ASTM D1003-77. SUNGLAZE panels are warranted for up to 10 years from the date of purchase not to break or fail as a result of impact by hail measuring up to 20mm in diameter, in speed of up to 21m/s.

Please note: Warranties only apply to installations and maintenance that follow Palram installation instructions and specifications.

All marketing materials and any content therewith provided by Palram® are provided solely for the purpose of supporting and enhancing the marketing of Palram® products.

These materials are protected by Palram's intellectual property rights and may not be used for any other purpose or in connection with the sale of products of any other manufacturer.

These materials may not be transferred to or used by any third party without prior permission of Palram.



www.palram.com

In as much as Palram Industries has no control over the use to which others may put the material, it does not guarantee that the same results as those described herein will be obtained. Each user of the material should make his own tests to determine the material's suitability for his own particular use. Statements concerning possible or suggested uses of the materials described herein are not to be construed as constituting a license under any Palram Industries patent covering such use or as recommendations for use of such materials in the infringement of any patent. Palram Industries or its distributors cannot be held responsible for any losses incurred through incorrect installation of the material. In accordance with our company policy of continual product development you are advised to check with your local Palram Industries supplier to ensure that you have obtained the most up to date information.

© 2025 Palram Industries Ltd. | SUNGLAZE® is trademark of Palram Industries Ltd.



606364 - 08/2026